


HUSKY OIL COMPANY  
~~8~~ FEDERAL #12  
Eddy County, New Mexico

TEN-POINT PROGRAM TO ACCOMPANY FORM 9-331C

1. Surface Formation: Surface sands, gypsum, dolomite
2. Important Geological Formations:

Queen	650
Grayburg	1000
San Andres	1425
Glorieta	2725
Tubb	4090
Abo	4830
Bursum	6825
Strawn	7890
Atoka	8285 (-4770)
Morrow	8360
Mississippian	8550



3. Gas is expected in the Atoka @ 8285' and in the Grayburg @ 1000'.

4. Casing Program:

13-3/8", 48# per ft., K-55 ST&C new casing to apprx. 300';  
8-5/8", 24# per ft., K-55, LT&C to apprx. 1500'; 5-1/2" ~~40.5#~~ 15.5#  
& ~~44.6#~~ 17 per ft., K-55 & N-80, LT&C to apprx. 8600'.

5. Pressure Control:

13-3/8" X 12" nominal 3000 psi slip-on and weld, flanged casing head for drilling below surface casing.

12", 900 Series, 3000# W.P. Dual Ram Hydraulic Blowout Preventers for drilling below surface casing. All choke lines, choke manifold, valves, fitting, etc. will have a minimum pressure rating of 3000 PSI.

A 3000# W.P. Hydril will be added before drilling below 8-5/8" casing.

All BOP equipment will be pressure tested to a minimum of 100% of rated working pressure or 70% of internal yield (whichever is less) prior to drilling out the surface casing shoe.

6. Mud Program:

0 - 300': Mud at company discretion to maintain good hole