

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or to test a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR
HUSKY OIL COMPANY

3. ADDRESS OF OPERATOR
600 S. Cherry St., Denver, CO 80222

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FNL & 1980' FWL, NE NW
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE

NM 17215

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Husky Federal

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Diamond Mound, Atoka

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 15-16S-27E

12. COUNTY OR PARISH
Eddy

13. STATE
New Mexico

14. API NO.
30-015-23731

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3568' GR

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)

RECEIVED
JUN 16 1981

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged with a total of 448 sx Class "H" cmt as instructed by John Wade, USGS, Artesia, New Mexico and George Stewart, USGS, Albuquerque, New Mexico on 8/3/81 as follows:

Plug #1: 8300'-8600' - 146 sx Class "H" cmt + 2% CaCl₂.
Plug #2: 6050'-6250' - 100 sx Class "H" cmt + 2% CaCl₂. WOC.
Tagged cement at 6020'.
Plug #3: 2660'-2860' - 132 sx Class "H" cmt + 2% CaCl₂.
Plug #4: 1450'-1550' - 50 sx Class "H" cmt + 2% CaCl₂. WOC.
Tagged Cmt @ 1430'.

Surface Plug: - 20 sx Class "H" cmt + 2% CaCl₂.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE Engr. Assistant DATE August 5, 1981
for Vera Chandler

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE 6-13-86
CONDITIONS OF APPROVAL, IF ANY: