

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM -28007	
2. NAME OF OPERATOR Yates Petroleum Corporation		6. INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR 207 South 4th St., Artesia, NM 88210		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with State requirements. See also space 17 below.) At surface 330' FNL & 1650' FWL		8. FARM OR LEASE NAME Sivley "PY" Federal	
14. PERMIT NO.		9. WELL NO. 1	
15. ELEVATIONS (Show whether Dr., R., or S.) 3825.5' GR		10. FIELD AND POOL, OR WILDCAT Unit, West Henshaw	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit C, Sec. 9-T16S-R30E	
		12. COUNTY OR PARISH Eddy	
		13. STATE NM	

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Propose to plug and abandon this well in the following manner. Remove all down-hole equipment (RBP, pump, tools, tubing). Go in hole with tubing and spot cement plug from 3000' to 2850' (across Lovington perfs, 2925'-2958'). Pull tubing, pick up cement retainer, go back in hole & set retainer @ approximately 2770'. Squeeze 50-100 sacks Class "C" into Premier perfs, 2785'-2822'. Pull out of retainer and spot cement from top of retainer to 2600'. Pull up tubing and spot cement plug from 2407'-2250' (across Penrose perfs, 2345'-2357'). Pull up tubing and spot cement plug from 1200'-1100' (across base salt @ 1120'). Pull up tubing and spot cement plug from 575'-350' (across 7" casing shoe @ 575' and top salt @ 400'). Pull up tubing and place 15 sack plug at surface. Install regulation abandonment marker. All plugs will be Class "C" cement. Location will be restored in accordance with USGS-BLM requirements. Verbal approval for this plugging program was given by Mr. Stewart, USGS, Roswell on July 7, 1981.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineering Secretary

DATE

7-8-81

(This space for Federal or State office use)

APPROVED

(Orig. Sgd.) ROGER A. CHAPMAN

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY

JUL 9 1981

JAMES A. GILLHAM
DISTRICT SUPERVISOR

See Instructions on Reverse Side