

N.M.O.C.D. COPY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

C/O
SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐
well well other

2. NAME OF OPERATOR
Yates Petroleum Corporation /

3. ADDRESS OF OPERATOR
207 So. 4th St. - Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990' FNL & 330' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

XX

☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
NM 036191

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federales "BO"

9. WELL NO.

8

10. FIELD OR WILDCAT NAME
Eagle Creek San Andres

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit D, NMPM
Sec. 23-17S-25E,

12. COUNTY OR PARISH
Eddy

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3513' GR

RECEIVED
AUG 10 1981

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 1180'. Ran 29 joints of 7" 20# K-55 ST&C (1182') of casing set at 1180'. 1-notched guide shoe at 1180'. Flapper insert float at 1140'. Cemented w/150 sacks thixolite, 2# permacheck, 1/2# celloseal, 450 sacks 65-35 Poz, 2# permacheck and 1/4# celloseal. Tailed in w/150 sacks Class "C" 2% CaCl. PD 4:30 PM 8-2-81. Bumped plug to 750 psi, released pressure and float held okay. Cement did not circulate. WOC 6 hours. Ran Temperature Survey and found top of cement at 525'. Ran 1". Tagged cement at 544'. Spotted 100 sacks thixolite, 2# permacheck, 1/2# celloseal, 2% CaCl and 100 sacks Class "C" 3% CaCl. PD 2:15 AM 8-3-81. WOC 3 hours. Ran 1". Tagged cement at 445'. Spotted 100 sacks Class "C" 3% CaCl, 50 sacks thixolite, 2# permacheck, 1/2# celloseal and 2% CaCl. PD 6:30 AM 8-2-81. WOC 1-1/2 hours. (Cont

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED ROGER A. CHAPMAN

Engineering Sect'y DATE 8-6-81

ROGER A. CHAPMAN

This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL AUG 11 1981

TITLE _____ DATE _____

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side