

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 045818(a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hastie

9. WELL NO.

21

10. FIELD AND POOL, OR WILDCAT

Red Lake (O.G.SA)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 18-17S-R28E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

H & S Oil Company /

3. ADDRESS OF OPERATOR

216 American Home Bldg. - Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface:

660' FNL 1980' FWL of Section 18-T17S - R28E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

GR 3537.3

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/12/81 Ran 357' of 8 5/8" 23# Casing. Cemented with 225 sacks
Class C Cement w/Cal. Chloride, 113# Cello-seal & bentonite.
Circulated. Proposed 345' of casing 250 Sacks cement.

8/16/81 Ran 1798' of 5 1/2" 14# Casing. Cemented with 300 sacks
50/50 Poz w/D20 Bentonite, 900# D42 Kolite, 76# D29 Cello-flakes,
D112 38# Fluid loss additive, D65 13# Tic dispersant, D46
50# Anti-foam agent, CW100 10 bbl. Chemical Wash. Circulated.
Proposed 1800' casing 300 sacks cement.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Partner

DATE 8/19/81

(This space for Federal or State official use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL

AUG 24 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

AUG 20 1981