

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator MWJ Producing Company		Lease Dog Canyon 35 G State		Well # 1	
Location of Well	Unit G	Section 35	16S Township	27E Range	County Eddy
Drilling Contractor	1980/N 1892/E Tri-Service Drlg. Co.		Type of Equipment Rotary		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17"	13 3/8"	48#		420'	400
11"	* 8 5/8"	24 & 32#		1900'	1150
7 7/8"	4 1/2" or 5 1/2"	11# or 15.5 & 17#		9600'	350

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole 11" Size of Casing 8 5/8" Sacks cement required _____

Type of Shoe used guide Float collar used insert Btm 3 jts welded yes

TD of hole 1852' Set 1852' Feet of 8 5/8" Inch 24 # Grade J-SS

(New) used csg. @ 1852' with 200 270cc sacks neat cement around shoe
+ 1000 sax Hall. Lite additives 5# gel, 1/4# floerol, 8# salt

Plug down @ 6800 (AM) (PM) Date 9/17/61

Cement circulated Yes No. of Sacks 180 sx

Cemented by Hall & Burton Witnessed by Mike Stubbfield

Temp. Survey ran @ (AM) (PM) Date _____ top cement @ _____

Casing test @ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

centralizers @ 1812', 1772', 1692' lost daily break @ 1110'