

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN THE INDICATED\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM 18973

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NM OIL CONS. COMMISSION  
Artesia, NM 88210

8. FARM OR LEASE NAME

Eagle

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 15-T17S-R27E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

H & S Oil Company

3. ADDRESS OF OPERATOR

216 American Home Bldg.-Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)

At surface

1980 FNL 660 FEL of Section 15, T17S, R27E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

GR 3486.5

O. C. D.  
ARTESIA, OFFICE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10/23/81 Ran 344' of 8 5/8" 24#API Casing (Proposed 350'). Cemented with 250 sacks Class C Cement. Circulated 1 sack to pit.

10/30/81 Ran 1623' of 4 1/2" 11.5# Casing (Proposed 1750' of 5 1/2"). Cemented with 180 sacks Class C Cement and 180 sacks 50/50 Pos + 4% D20 + 3#/Sk. D24 + 1/4#/Sk D29 + 3% D112. Ran temp. survey as per USGS. Found cement top @ 1200'.

10/31/80 4 PM Started pumping down 1" outside the 4 1/2". Ran 262 Sk. Class C, 262 Sk. lite pos. Cement to surface.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Partner

DATE 11/13/81

(This space for initials or signature use)

APPROVED BY

CONDITIONS OF GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

TITLE

DATE

\*See Instructions on Reverse Side