

(May 1983)

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

OIL & GAS COMMISSION  
SUBMIT IN THE  
(Other) instructi  
verse side  
Artesia, NM 88210

Approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-18973

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Eagle

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 15-T17S-R27E

12. COUNTY OR PARISH 13. STATE

Eddy

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☐ GAS ☒ OTHER ☐  
WELL WELL

2. NAME OF OPERATOR

H & S Oil Company

3. ADDRESS OF OPERATOR

216

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)

At surface

1980 FNL 660 FEL of Section 15, T17S, R27E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

GR 3486.5

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*

11/9/81 Perforated @ 1541-45 1549-56 1 shot per ft.

11/10/81 Acidized w/750 gal. 15% acid - fraced w/32,000 gal.  
gelled water - 10,000 lbs FLA 100 - 30,000# 20-40  
sand - 4000# 10-20 sand

11/16/81 Pulled tubing set Bridge Plug @ 1520 W/5sk. cement plug  
on top.  
Perforated @ 1354-64 w/1 shot per ft.

11/17/81 Acidized w/500 gal 15% acid - fraced w/20,000 gal gelled  
water- 6000# FLA 100 - 17,000# 20-40 sand - 5000# 10-20 sand.

RECEIVED  
DEC 03 1981

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

ACCEPTED FOR RECORD

ROGER A. CHAPMAN

(This space for Federal or State office use)

APPROVED BY

DEC 11 1981

CONDITIONS OF APPROVAL, IF ANY:

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

TITLE Partner

DATE

TITLE

DATE

See Instructions on Reverse Side