U ED STATES SUBMIT IN TRIS OATEDEPARTMENT OF THE INTERIOR (Other Instructions on re-Budget Bureau No. 1004-0135 Form 3160-5 November 1983) Expires August 31, 1985 5. LEASE DESIGNATION AND ESSIAL NO. \tilde{r} ormerly 9-331) BUREAU OF LAND MANAGEMENTIA, NA 88210 M-14297 6. IF INDIAN, ALLOTTRE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELL'S CELYED (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT..." for such proposals.) 7. UNIT AGREEMENT NAME UEC 20 11 .2 111 183 OIL GAS WELL OTHER 8. FARM OR LEASE HAME NAME OF OPERATOR 045 OXY USA Inc. Citco Federal ARE 3. ADDRESS OF OPERATOR 9. WBLL NO. P.O. Box 50250 Midland, TX. 79710 LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) 10. FIELD AND POOL, OR WILDCAT At surface Eddy Cty Und. San Andres 11. BBC., T., R., M., OR BLK. AND MURYBY OR ARMA NWNE Sec 21 T16S R26E ARTESIA, OFFICE 430/N 2210/E Sec 21 T16S R26E 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 14. PERMIT NO. 12. COUNTY OR PARISE | 18. STATE Eddy 33551 NM16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF REPAIRING WELL PRACTURE TREAT MULTIPLE COMPLETE PRACTURE TREATMENT ALTERING CARING Χ SHOOT OR ACIDIZE ARANDON* SHOOTING OR ACIDIZING ABANDONMENT* REPAIR WELL CHANGE PLANS (Other) (Note: Report results of multiple completion on Well Completion or Recompletion Beport and Log form.) (Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones pertinent to this work.)* TD-1379' PBTD-1366' San Andres-1170'-1264' It is proposed to Plug and Abandon in the following manner: MIRU PU. TOOH w/rods & pump. ND WH, NU BOP. TOOH w/tbg. 1. RU wireline, RIH w/CIBP and set @ 1150'. RU dump bailer and dump 3 2. sx (43') on top of CIBP. RD wireline. TIH w/tbg OE to 1080' and circ hole w/9.5#/gal mud laden fluid. Spot 7 sx plug from 1080' to 979'. PU on tbg to 50' and spot 4 sx plug from 50' to surface. TOOH and LD tbg. Cut off wellhead & install dry hole marker. 15. I nereby certify that the foregoing is true and correct

*See Instructions on Reverse Side

TITLE

SIGNED

(This space for Federal or State office use)

CONDITIONS OF APPROVAL, IF ANY:

APPROVED ET Siened by thehier to talende

TIPLE Operations Manager

PETROLEUM ENGINEER

12/18/89

(Prepared by David Stewart)