

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator L. Texas Enterprises, Inc.		Lease So. Red Lake Gb. Ut.		Well # 43	
Location of Well	Unit K	Section 36	Township 17S	Range 27E	County Eddy
Drilling Contractor	1650/S 1650/W Stewart Bros. Drlg. Co.		Type of Equipment Rotary		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
* 12 1/4"	8 5/8"	24 #		450'	450
* 7 7/8"	4 1/2"	9.5 #		1800'	465

Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_  
(Approved) (Rejected)

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole 7 7/8 Size of Casing 4 1/2 Sacks cement required \_\_\_\_\_

Type of Shoe used guide Float collar used insert Btm 3 jts welded yes

TD of hole 1764 Set 1790 Feet of 4 1/2 Inch 9.5 # Grade K-SS, ST & C

(New-used csg. @ 1764 with 460 sacks neat cement around shoe 0.2 3 CR 2  
+ \_\_\_\_\_ sax \_\_\_\_\_ additives \_\_\_\_\_

Plug down @ 4:00 (AM) (PM) Date 10/3/81

Cement circulated NO No. of Sacks \_\_\_\_\_

Cemented by HALLIBURTON Witnessed by Harry Brooks

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: ★ PARTED CSG, DID NOT BUMP PLUG.

CSG. RTD @ 1st Collar. Opr. will notify of intentions