

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 15007

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Bear Draw

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Bear Draw Q.G.S.A.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 28 T16S R29E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Forister & Sweatt

3. ADDRESS OF OPERATOR

PO Box 161, Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980 FSL 1980 FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3634 G.L.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

surface & oil string casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drilled 12½" hole to 343'. Ran 8 jts 333' of 8 5/8" 20# I.B. Foster casing set at 343'. Cemented with 225 sx Class C with 2% CCI. Plug down 6:30 a.m. 02/02/82. Did not circulate. Ran 1" pipe topped cement at 90'. Cemented through 1" pipe with 150 sx Class C 2% CCI. Cement circulated.

2. Drilled 7 7/8" hole to 2800'. Ran 69 jts 2816' of 4½" 9.5# 8 round casing set at 2800'. Cemented with 800 sx Hal Light with 5# Gtl ½# Flocele 8# salt followed with 200 sx 50-50 PO2 with 2% gel 6# salt 3/10 of 1% CFR2. Plug down 1:45 a.m. 02/08/82. Cement top at 630'.

RECEIVED
FEB 17 1982OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Partner

DATE

02/16/82

(This space for Federal or State Record)

ROGER A. CHAPMAN

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

FEB 19 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side