

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Eagle Oil & Gas Co.

3. ADDRESS OF OPERATOR

510 Hamilton Bldg. Wichita Falls, TX 76301

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) Unit <sup>T</sup>

AT SURFACE: 2310' FSL and 660' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐


MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) ☐

SUBSEQUENT REPORT OF:



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Yucca Drilling Co. rigged up and spudded at 3:45 p.m., December 12, 1981. Drilled a 12 1/4" hole to 415 feet, ran 8-5/8", 24#, K-55 casing set at 404 feet DF. Cemented with 250 sx Class "C" cement, circulated to surface. WOC 14 hours tested to 1000 psi for 30 min. with no pressure loss. Resumed drilling 7-7/8" hole at 1:45 p.m. on December 13, 1981.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Samuel H. Hays*  
FOR THE CHAIRMAN

TITLE

Petroleum Engineer

DATE

1-6-82

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

JAN 11 1981

TITLE

DATE

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO