

UNITED STATES OIL CONS. COM.
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

CKF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
Eagle Oil Company
3. ADDRESS OF OPERATOR
3000 N Garfield, Suite 210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
Unit I
AT SURFACE: 2,310' FSL and 660' FEL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

RECEIVED BY
JUN 16 1986
O. C. D.
ARTESIAN

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:
TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) _____

SUBSEQUENT REPORT OF:
☐
☐
☐
☐
☐
☐
☐
☐
☒

APR 18 1982
U.S. GEOLOGICAL SURVEY

5. LEASE
NM8940
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Crow Flats
9. WELL NO.
2
10. FIELD OR WILDCAT NAME
Wildcat
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA
Sec. 19, T. 19N, R. 28E
12. COUNTY OR PARISH
Eddy
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DE KDB AND WD)
3,604' DF

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-1-82 MI and RU Mack Chase Unit. Installed lubricator on top of 35bbls. mud and loaded 4-1/2" casing. Set CIBP at 1,700' and dumped 35' of neat cement on plug. Ran free point, 4-1/2" casing free at 900'. Cut off at 900' with 9.5 ppg mud. Spot 25 sack neat cement plug at 887'.
4-2-82 Spot 35 sack neat cement plug at 435'. Laid down 4-1/2", 10.5#/ft., 8rd., ST&C, K-55 casing. Left point 4-1/2" casing in hole. Spot 15 sack neat cement plug from 30' to surface. Installed well marker, cemented marker in top of 4-1/2" RD and released Mack Chase unit @ 10:30am 4-2-82. Well plugged and abandoned.

Subsurface Safety Valve: Manu. and Type _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. E. Brown TITLE Agent DATE _____

(This space for Federal or State office use)

APPROVED BY Mark Horn TITLE Agent DATE _____
CONDITIONS OF APPROVAL, IF ANY:

Post FD-2
6-20-86
P417