

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>JOHN P. PARRISH</u>		Lease <u>BEDINGFIELD</u>		Well # <u>1</u>	
Location of Well	Unit <u>330 N 230 W D</u>	Section <u>22</u>	Township <u>16</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor	<u>S & B DRING CO.</u>		Type of Equipment <u>Rotary 12/15/81</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	12 3/4	36 #	.	400'	300 SxS. CIRC
11	8 5/8	24 #		1100'	650 Sx. Circ.
7 7/8	4 1/2 or 5 1/2	9.5# or 14#		1400'	300 SxS.

Casing Data:

Surface 27 joints of 8 5/8" inch 24 # Grade J-55

(Approved) (Rejected)

Inspected by Larry Brooks date 12/25/81

Cementing Program

Size of hole 11" Size of Casing 8 5/8" Sacks cement required 400

Type of Shoe used guide Float collar used inst. Btm 3 jts welded yes

ID of hole 1132 Set 1095 Feet of 8 5/8 Inch 24 # Grade J-55

New-used csg. @ 1095 with 100 sacks neat cement around shoe cl. Cw/2% CaCl + 300 sax Halliburton Lite additives W/ 1/4 #/sk. flocc.

Plug down @ 11:00 (AM) (PM) PM Date 11/25/81

Cement circulated yes No. of Sacks 100

Cemented by HALLIBURTON Witnessed by LARRY BROOKS.

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Could not run last jt. to 1132' landed csg. @ 1095