

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

C/SF  
**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
Amoco Production Company ✓
3. ADDRESS OF OPERATOR  
P. O. Box 68, Hobbs, New Mexico 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1650' FEL x 660' FNL, Sec. 12  
AT TOP PROD. INTERVAL: (Unit B, NW/4, NE/4)  
AT TOTAL DEPTH:


16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

- ☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Moved in service unit 2-4-82 (Baber 52). Ran 2-3/8" tubing and 4-1/2" bit and cleaned out hole to 9505'. Circulated hole with 250 barrels 2% KCL water. Pulled tubing and bit. Ran Vann System with 5-1/2" packer and 2-3/8" tubing. Packer set at 9217'. Perforated intervals 9325'-29', 9352'-66', and 9396'-9400' with 4 JSPF. Flowed well 4 hours. Recovered 3 ft. flare. Acidized well with 2500 gallons 7-1/2% MS with 1000 SCF N2/barrel. Flushed with 23 barrels 2% KCL water with 1000 SCF N2/barrel. Flowed back 45 minutes, recovered 5 barrels water. Swab tested 4 hours, recovered 10 barrels of load water. Flow tested 16 hours. Recovered 3 BW, 2 BO, and a 30 ft. flare. Moved out service unit 2-15-82. Currently evaluating.

0+6-USGS, R 1-Hou 1-W. Stafford, Hou 1- DMF 1-Susp

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Mark Hanna TITLE Ast. Adm. Analyst DATE 2-19-82

RECEIVED FOR RECORD  
ROGER A. CHAPMAN  
APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

FEB 24 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side