

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
NTA FE	1
LE	1
S.G.S.	
ND OFFICE	
ERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

APR 1 1982

O. C. D.

ARTESIA OFFICE

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
		5. State Oil & Gas Lease No. LG 5993
OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
Name of Operator Collier Energy, Inc. ✓		8. Farm or Lease Name SRC State
Address of Operator P. O. Box 798, Artesia, New Mexico 88210		9. Well No. #1
Location of Well UNIT LETTER N 330 FEET FROM THE South LINE AND 1650 FEET FROM THE West LINE, SECTION 23 TOWNSHIP 17S RANGE 28E NMPM.		10. Field and Pool, or Wildcat East Empire Yates Seven Rivers
15. Elevation (Show whether DF, RT, CR, etc.) 3674' GL		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

FORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
REPAIR OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

January 29, 1982: Spudded well with 10" bit.  
February 8, 1982: Drilled to 275' and ran 8 5/8" 23# casing to 275'. Cemented with 100 Sxs of Class "C" cement with 2% CaCl<sub>2</sub>. Didn't circulate. TOC at 180' and filled to surface with 4 yards of ready mixed. WOC 18 hours.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Loren R. Peppard TITLE Agent DATE 3-29-82

APPROVED BY Mike Wulfa TITLE OIL AND GAS INSPECTOR DATE APR 1 1982

CONDITIONS OF APPROVAL, IF ANY: