NM OIL C 'S. COMMISSION Drawer D.

AUNITED STATES 210

rorm A	pproved			
Budget	Bureau	No.	42-R1	42

AUNITED STATES 210	5. LEASE			
DEPARTMENT OF THE INTERIOR	NM-05855			
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME			
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME			
1. oil gas other	Government			
2. NAME OF OPERATOR OCT 19 1982	9. WELL NO. No. 6			
John H. Trigg	10. FIELD OR WILDCAT NAME			
3. ADDRESS OF OPERATOR	Undesignated			
Box 520, Roswell, New Mexico 88262 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA			
below.)	Sec. 25-T16S-R28E			
AT SURFACE: 2310' FNL & 660' FEL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE Eddy N.M.			
AT TOTAL DEPTH:	14. API NO.			
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,				
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3702.7 G.L.			
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: \square	7056759111			
FRACTURE TREAT	MERSELLINE			
REPAIR WELL	(NOTE: Repend results of multiple dempletion or zone			
PULL OR ALTER CASING	change on Forth 14-330.)			
CHANGE ZONES	131 ON 8 CAR (1975)			
ABANDON*	arologica			
(other) Surface, Intermediate & Production Casing	U.S. CFOWGILL REVIEW TO THE			
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen 2/3/82: Drilled to a T.D. of 328'. Ran 325'	irectionally drilled, give subsurface locations and to this work.)* of 8-5/8", 20 lb. casing.			
Cemented with 100 sx Class "C" cemer	it, 2% tati.			
2/7/82: Drilled out plug and 50' cement.				
3/1/82: Drilled to a T.D. of 1610'. Ran 1610' of 7", 18 lb. casing. Circualted 6 sxs of gel, 100 lbs. gel. Set.				
3/5/82: Drilled to a T.D. of 1657'. Bailed hole dry, water shut off.				
3/13/82: Drilled to T.D. of 1900'. Ran 1898' Cemented with 100 sx Class "C", 50-5				
Subsurface Safety Valve: Manu. and Type	Set @ Ft.			
18. I hereby certify that the foregoing is true and correct				
SIGNED MARK ACCEPTED THE Agent				
(ORIG. SGD.) DAVID R. GLASS	ice use)			
APPROVED BY CONDITIONS OF APPROVALUE AND 1982	DATE			
U.S. GEOLOGICAL SURVEY				
DOSWELL NEW MEXICO				
ROSVVLLI, 14114 See Instructions on Reverse S	Side			