

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIP
(Other instructions on reverse side)

Form approved
Budget Bureau No. 42-R1424

C/SF

Artesia, NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different depth. Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

NM 15868

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Empire West ~~Unit~~
Federal Com

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Empire ~~Narrow~~ ~~Perm~~

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 25 T-17S R-27E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

MAR 11 1982

3. ADDRESS OF OPERATOR

Holly Energy Inc. /

O. C. D.
ARTESIA, OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See space 17 below.)

P.O. Box 726 Artesia, New Mexico 88210

At Surface

1650 FSL & 2310 FWL Section 25 T-17S R-27E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3581.6

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐ ABANDON* ☐
REPAIR WELL ☐ CHANGE PLANS ☐
(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☐
(Other) ☒ Spud & set surface ☒

17. DRILL PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud well 12:15 p.m. 2-23-82

Drill 17½" hole to 425', set 423' 13-3/8 48# H-40 STC casing.
Cement with 200 sacks Class C with 1/4# Celo-seal 1# perma-check, 300 sacks Class C 1# perma-check 2% calcium chloride.
Plug down @ 12:00 p.m. 2-24-82.
Did not circulate, after waiting 6 hours run temperature survey, found T.O.C. @99'.
Run 1" to 86', cement with 100 sacks Class C 3% calcium chloride.
Circulate 25 sacks to pit.

RECEIVED
MAR 3 1982

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Robert Lloyd

TITLE Superintendent

DATE 2-26-82

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE:

ACCEPTED FOR RECORD

DATE

MAR 10 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side