

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		NM OIL CONS COMMISSION	
2. NAME OF OPERATOR MWJ Producing Company		Drawer DD Artesia, NM 88210	
3. ADDRESS OF OPERATOR 400 W. Illinois, Midland, Tx. 915/682-5216		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit Letter C, 467' FNL & 2310' FWL		8. FARM OR LEASE NAME Roper Federal	
14. PERMIT NO.		9. WELL NO. 1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3538' GL		10. FIELD AND POOL, OR WILDCAT Empire Y-SR	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 25, T-17-S, R-27-E	
		12. COUNTY OR PARISH Eddy	
		13. STATE NM	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

P&A well as per instructions by Adam, BLM, Carlsbad.

1. Pulled tubing & rods.

2. 11-16-93: Pump 5 bbls fresh water down casing. Pump 50 sx Class "C" cement + 2% CACL. Pressure up to 750#. Close valve on swedge. Cement plug from top to bottom..

3. Installed dry hole marker.

4. Restore location.

RECEIVED
MAR 21 1994
P&A

18. I hereby certify that the foregoing is true and correct

SIGNED Donna Burkart

TITLE Donna Burkart, Agent

DATE 1-4-94

(This space for Federal or State office use)

APPROVED BY Shannon J. Shaw

TITLE PETROLEUM ENGINEER

DATE 3/18/94

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side