

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DEPT. REC-30

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501
JUN 7 1982

O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-78

1a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B-2179	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Ray Westall ✓	8. Farm or Lease Name Hudson State
3. Address of Operator P.O. Box 4 Loco Hills, NM 88255	9. Well No. 2
4. Location of Well UNIT LETTER J 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 9 TOWNSHIP 17S RANGE 28E N.M.P.M.	10. Field and Pool, or Whichever Red Lake Q-G-SA
15. Elevation (Show whether DF, RT, GR, etc.) 3533. GR	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

May 24, 1982 - Spud well with 12 1/4" bit.

May 25, 1982 - Ran 323' of 8 5/8" 20# 8 rd casing. Cemented with 220 sx of Class "C", 2% CaCl. WOC. Test BOP to 1000# for 30 min. Held O.K. 18HR. Changed to 7 7/8" bit.

May 29, 1982 - T.D. 2500'. Ran 2500' of 4 1/2" 9.5#, J-55 casing. Cemented with 550 sx of 50-50 Poz "C", 6% CF-9, 3% TF-4, 3% KCL. Circulated to surface.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ray Westall TITLE Operator DATE 6-4-82

APPROVED BY [Signature] TITLE OIL AND GAS INSPECTOR DATE JUN 11 1982

CONDITIONS OF APPROVAL, IF ANY: