

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR
Forister & Sweatt

3. ADDRESS OF OPERATOR
PO Box 161, Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: **990 FNL 1650 FEL**

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

☐
☐
☐
☐
☐
☐
☐
☐

(other) **casing program used**

5. LEASE

NM 15007

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Bear Draw

9. WELL NO.

3

10. FIELD OR WILDCAT NAME

Bear Draw Q.G.SA.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 28 T16S R29E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3638.7 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spudded 8:30 a.m. June 30, 1982. Drilled 12½ hole to 334 ft. Ran 323 ft. 8 5/8" 20# casing set at 334 ft. Cemented with 50 sx H.L. Thick set with 2% Cal Cl and ½# Flo seal and 200 sx Class C with 2% Cal Cl. Plug down 8:00 p.m. July 1, 1982. Circulated 100 sx cement to pit.

2. Drilled 7 7/8 hole to 2655'. Ran 2655 ft. 4½" 11.6# casing set at 2655 ft. Cemented with 550 sx H.L. with 6# salt ½# Flocele and 260 sx Class C 50/50 Poz with 2% gel and 6# salt. Plug down 3:00 a.m. July 5, 1982. Circulated 30 sx to pit.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Clayton Fournier

TITLE

Partner

DATE

July 8, 1982

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: