

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED

AUG 02 1991

O. C. D.  
ARTESIA, OFFICE

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other RECOMPLETION

2. Name of Operator  
YATES PETROLEUM CORPORATION

3. Address and Telephone No.  
105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
Unit N, 660' FSL, 2310' FWL, Sec. 21-T17S-R27E

5. Lease Designation and Serial No.

NM 12690

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Estelle TA Federal #1

9. API Well No.

30-015-24172

10. Field and Pool, or Exploratory Area

Undes. Abo

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☒ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

7-10-91. RUPU. Test casing. Set CIBP 9065' and cap with 35' cement. Perforated 2 squeeze holes @ 5450'. No indication of communication between 8-5/8" and 4-1/2". Set SVEZ drill retainer at 5356'. Pump 500 g. Surebond. Mix and pump 550 sx Super "C" cement. Tail in w/350 sx Class "C" Neat. Sting out of retainer. Reverse 13 sx cement to pit. TOH with tubing. WOC. Drill retainer at 5356'. Test squeeze perfs to 500 psi for 15 minutes, OK. Displace hole w/2% KCL. TOH. Perforated 5069-5185' w/20 - .42" holes as follows: 5069, 74, 76, 81, 84, 92, 98, 5101, 07, 10, 19, 27, 30, 36, 46, 50, 62, 78, 81, and 5185'.  
7-16-91. Acidized perfs 5069-5185' w/5000 gals 20% NEFE acid.  
7-19-91. Reacidized (via 2-3/8" tubing) with 20000 gals 20% NEFE gelled acid and 30 ball sealers.

14. I hereby certify that the foregoing is true and correct

Signed *[Signature]*

Title Production Supervisor

Date 7-26-91

(This space for Federal or State office use)

Approved by  
Conditions of approval, if any:

Title

ACCEPTED FOR RECORD

Date 8/3/91

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

CARLSBAD, NEW MEXICO

\*See instruction on Reverse Side