

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or reworked well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Penn. 30 through 34 shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
Lower							
T. Anhy	T. Canyon	7517	T. Ojo Alamo	T. Penn. "B"			
T. Salt	T. Strawn	8013	T. Kirtland-Fruitland	T. Penn. "C"			
T. Salt	T. Atoka	8352	T. Pictured Cliffs	T. Penn. "D"			
T. Yates	T. Miss		T. Cliff House	T. Leadville			
T. 2 Rivers	T. Devonian		T. Menefee	T. Madison			
T. Queen	T. Silurian		T. Point Lookout	T. Elbert			
T. Grayburg	T. Montoya		T. Mancos	T. McCracken			
T. San Andres	T. Simpson	1013	T. Gallup	T. Ignacio Qtzte			
T. Glorieta	T. McKee	2400	T. Base Greenhorn	T. Granite			
T. Paddock	T. Ellenburger		T. Dakota	T.			
T. Blinbry	T. Gr. Wash		T. Morrison	T.			
T. Tebb	T. Granite		T. Todilto	T.			
T. Drinkard	T. Delaware Sand		T. Entrada	T.			
T. Abo	T. Bone Springs	4439	T. Wingate	T.			
T. Wolfcamp	T. Morrow Clastic	5651	T. Chinle	T.			
T. Penn.	T. Chester	8792	T. Permian	T.			
T. Cisco (Bough C)	T.	6432	T. Penn. "A"	T.			

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
 No. 2, from.....to.....
 No. 3, from.....to.....
 No. 4, from.....to.....
 No. 5, from.....to.....
 No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....
 No. 4, from.....to.....feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	790	790	Surface, Redbeds				
790	1160	370	Redbeds, Sand				
1160	1511	351	Redbeds, Dolomite				
1511	4375	2864	Dolomite				
4375	4849	474	Dolomite, Shale				
4849	5237	388	Dolomite				
5237	5371	134	Dolomite, Lime				
5371	8875	3504	Lime, Shale				