Drawer DD rtesia, NM 88210

Form Approved.

Budget Bureau No. 42-R1424

UNITED STATES DEPARTMENT OF THE INTERIOR

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	5. LEASE NM 0219603-A 6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to be pen or plug back to a different reservoir. Use Form 9–331–C for such proposals. 1. oil gas well other	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME Federal BW	
2. NAME OF OPERATOR Yates Petroleum Corporation ColCal Survey	9. WELL NO. 13 1982	
3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME C. D. Eagle Creek SARTESIA, OFFICE	
207 So. 4th St., Artesia, NM 88210 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit P, Sec. 22-T17S-R25E	
AT SURFACE: 990 FSL & 330 FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	12. COUNTY OR PARISH 13. STATE NM	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	14. API NO.	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3508' GR	
TEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zone change on Form 9–330.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran 37 jts of 4-1/2" 9.5# J-55 casing set at 1478'. 1-ball float shoe set TD 1500'. 1478'. Cemented w/175 sacks Class C 50/50 Poz, 2% gel, 3#/salt, .2% CFR-2, .10% Halad-4 w/2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 2:15 PM 9-15-82. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 15 sacks. WOC 96 hours. WIH and perforated 1301-1440' w/32 .50" holes in 2 stages as follows: Stage I: 1313, 24, 37, 44, 54, 62, 77, 86, 96, 1403, 16, 24 and 35' (13 holes). Stage II: 1301, 10, 17, 21, 27, 32, 41, 47, 50, 57, 60, 65, 82, 91, 99, 1406, 20, 29 and 40' (19 holes). Frac'd perfs 1301-1440' w/60000 gallons gelled 1% KCL water and 120000# (110000# 20/40 sd,10000# 100 mesh) sand, 2000 gallons 15% NEA acid. Ran tubing, rods & pump. Pumping back load.

Subsurface Sa	fety Valve: Manu. and Type		Set @ Ft.
18. I hereby co	ertify that the foregoing is true and	correct	
SIGNED 1 . Q	ACCEPTED FOR RECORD	LE Engineering Secty	DATE 9-28-82
APPROVED BY CONDITIONS OF	Nother.	cace for Federal or State office use)	. DATE
	U.S. GEOLOGICAL SURVEY		
_	ROSWELL, NEW MEXICOS		