Form Approved. Budget Bureau No. 42-R1424

UNITED STATES

Artesia, NM 88219 LEASE

NM 021963

DEPARTMENT OF THE TERROR TO THE	NM 021963	
GEOLOGICAL SHRYE	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
	Mirs.	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug black desifferent reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT N	AME RECEIVED
1 oil gas OIL & GAS	8. FARM OR LEASE NAME Federal BZ OCT 26 1982	
well W well other MINERALS MGMT. SERVICE	9. WELL NO.	
2. NAME OF OPERATOR ROSWELL, NEW MEXICO	19	O. C. D.
Yates Petroleum Corporation 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAMEESIA, OFFICE Eagle Creek SA 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit B, Sec. 28-T17S-R25E	
207 South 4th St., Artesia, NM 88210		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 330 FNL & 1650 FEL, Sec. 28-17S-25E AT TOP PROD. INTERVAL: AT TOTAL DEPTH:		
	12. COUNTY OR PARISH Eddy	
	14. API NO.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
	15. ELEVATIONS (SHOW 3558 GR	DF, KDB, AND WD)
SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)	(NOTE: Report results of multiple completion or zone change on Form 9–330.)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertined udded a 14-3/4" hole at 9:30 AM 10-4-82. Set 35' 10-3/4" 40.5# K-55 ST&C casing set at 343'. 1-T insert valve set at 303'. Cemented w/225 sx Class amped plug to 1000 psi, released pressure & float once of the content of the con	irectionally drilled, give substitution this work.)* of 20" conductor gexas Pattern guide C w/3% CaCl. PD 4 held okay. Cement ement at 60'. Ran irculated 5 sacks nutes. Cut off & sumed drilling. Reched guide shoe se sx Pacesetter Lite lass C 2% CaCl2. Co. Bumped plug to acks. WOC. Drilled	pipe. Ran 9 jts shoe set at 343'. :30 PM 10-4-82. did not circulate. 1". Cemented w/65 to pit. WOC. welded on flow an 29 jts of 7" 20# t 1100'. Insert , 5#/sx gilsonite, ompressive strength 800 psi, released out 11:30 AM 10-6-8
and the state of t		
SIGNED CHARLES FOR RECORD Engineering S		
(This space for redefal of State of		
APPROVED BY (ORIG. SGD.) DAVID R. GLASS CONDITIONS OF APPROVACITATIVE 1002	DATE	

U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO See Instructions on Reverse Side