STATE OF NEW MEXICO				
ENERGY AND MINERALS DEPARTMENT OIL CONSERVATION DIVISION				
DISTRIBUTION P. O. BOX 2088	RECEIFLY Form C-103 Revised 10-1-78			
SANTA FE SANTA FE, NEW MEXICO 87501				
U.S.O.S.	Chan Inducate Type of Lease			
	5. State Oli 6 Gas Lease No. O. C. D:			
SUNDRY NOTICES AND REPORTS ON WELLS 100 NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OF PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" FORM C-101) FOR SUCH PROPOSALS.)	ARTEGALOFTICE			
I. OIL X GAB OTHER-	7. Unit Agreement Name			
2. Name of Operator Yates Petroleum Corporation	8. Farm or Lease Hame Winters DN			
3. Address of Operator	9, Well No. 3			
207 South 4th St., Artesia, NM 88210	10. Field and Pool, or Wildcat			
UNIT LETTER A 330 FEET FROM THE LINE AND FEET FROM THE	Eagle Creek SA			
East 14 17S 25F				
THE East LINE, SECTION 14 TOWNSHIP 17S RANCE 25E NMP				
XIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	12. County			
3472' GR	Eddy AllIIIII			
Check Appropriate Box To Indicate Nature of Notice, Report or C NOTICE OF INTENTION TO:	Other Data NT REPORT OF:			
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING			
PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB X				
OTHER				
отися				
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, includi work) SEE RULE 1103.	ng estimated date of starting any proposed			
Spudded a 14-3/4" hole at 1:00 PM 10-10-82. Set 40' of 20" conductor p	Dipe. Ran 9 its of $10-3/4$ "			
40.5# K-55 ST&C casing set at 358'. 1-Texas Pattern notched guide shoe set at 358'. Insert float				
set at 318'. Cemented w/225 sx Class C 3% CaCl <sub>2</sub> . Compressive strength	n of cement - 1275 psi in			
12 hrs. PD 11:45 PM 10-10-82. Bumped plug to 1000 psi, released press Cement circulate 10 sacks. WOC. Drilled out 12:15 PM 10-11-82. WOC 1				
& welded on flow nipple. Reduced hole to 9-7/8". Drilled plug & resume				
7" 20# casing set at 1158'. 1-Texas Pattern notched guide shoe at 1158	B'. Insert float at 1118'.			
Cemented w/100 sx Thixolite, 1/4# celloseal, 200 sx Pacesetter Lite C,				
<pre>seal &amp; 3% CaCl<sub>2</sub>. Tailed in w/150 sx Class C 2% CaCl<sub>2</sub>. Compressive str in 12 hrs. PD 11:00 AM 10-12-82. Bumped plug to 1000 psi, released pr</pre>				
Cement did not circulate. WOC 6 hrs. Ran Temperature Survey & found t				
1". Tagged cement at 500'. Spot'd 75 sx Class C 3% CaCl <sub>2</sub> . PD 8:00 PM	1 10-12-82. WOC 2 hrs. Ran			
1". Tagged cement at 460'. Spot'd 50 sx Class C 3% CaCl <sub>2</sub> . PD 10:30 PM				
Ran 1". Tagged cement at 500'. Spot'd 50 sx Class C 3% CaCl <sub>2</sub> . PD 2:3 Ran 1". Tagged cement at 480'. Spot'd 50 sx Class C 3% CaCl <sub>2</sub> . PD 3:0				
Ran 1". Tagged cement at 480'. Spot'd 25 sx Class C 3% CaCl <sub>2</sub> . PD 5:1				
Ran 1". Tagged cement at 420'. Spot'd 25 sx Class C 3% CaCl <sub>2</sub> . PD 7:3				
Ran 1". Tagged cement at 415'. Spot'd 225 sx Class C 3% CaCl2. PD 10: circulated 10 sx. WOC. Drilled out 1:00 PM 10-13-82. WOC 26 hrs. NU &				
Reduced hole to 6-1/4". Drilled plug & resumed drilling. 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	tested to 1000 psi, okay.			
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
escale in anota Dor Alite Time Engineering Secretary	10_10_00			
Alexed The Andder of Carling Title Engineering Secretary	DATE <u>10-18-82</u>			
<i>v</i>				
APPROVED BY YITLE	DCT 2 8 1982			
CONDITIONS OF APPROVAL, IF ANY:				

ONDITIONS	٥F	APPROVAL.	15	ANY
-----------	----	-----------	----	-----