OIL CONSERVATION DIVISION DISTRIBUTION BANTAFE OIL CONSERVATION DIVISION P. O. BOX 2088 SANTAFE	RECHNIED Form C-103 Revised 10-
	DE Ingeone Bar at Leose
LAND OFFICE	State For For
	ARTESIA, OFFICE
SUNDRY NOTICES AND REPORTS ON WELLS WE THIS FORM FOR PROPAGALS TO CALLE ON TO DELPTH OF PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR FERMIT -" (FORM CHOIL FOR SUCH PROPOSALE.)	
01L [17] 6AB	7. Unit Agreement Rome
WELL A WELL OTHER.	8. Farm or Lease Hame
Yates Petroleum Corporation	Winters DN
Address of Operator 207 South 4th St., Artesia, NM 88210	9. Well No. 3
Location of Well	J 10, Field and Pool, or Wildcat
UNIT LETTER P 330 FLET FROM THE South LINE AND 990 FLET FR	
THE East LINE, SECTION 14 TOWNSHIP 178 RANGE 25E	•••• <u>() </u>
Milling (Control of the second state of the se	12. County
3472' GR	Eddy
Check Appropriate Box To Indicate Nature of Notice, Report or C NOTICE OF INTENTION TO:	Other Data NT REPORT OF:
RY DR M REMEDIAL WORK	ALTERING CASING
MPORARILY ABANDON COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
CHANGE PLANS CASING TEST AND CEMENT JOB CONTRACT PRODUCTION CONTRACT PRODUCTION CONTRACT	asing.
OTHER	
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, includi	ing estimated date of starting any prop
work SEE RULE 1103.	
TD 1500'. Ran 37 joints of 4-1/2" 9.5# J-55 casing set at 1489'. 1489'. Cemented w/200 sacks Class "C" with 4% gel, 3# salt, 2% Ca .1% Halad-4. Compressive strength of cement - 1250 psi in 12 hour 10-18-82. Bumped plug to 1000 psi, released pressure and float he circulated 15 sacks to pit. WOC 18 hours. Waiting on completion	aCl ₂ , .2% CFR-2, rs. PD 12:30 PM eld okay. Cement
TD 1500'. Ran 37 joints of 4-1/2" 9.5# J-55 casing set at 1489'. 1489'. Cemented w/200 sacks Class "C" with 4% gel, 3# salt, 2% Ca .1% Halad-4. Compressive strength of cement - 1250 psi in 12 hour 10-18-82. Bumped plug to 1000 psi, released pressure and float he	aCl ₂ , .2% CFR-2, rs. PD 12:30 PM eld okay. Cement
TD 1500'. Ran 37 joints of 4-1/2" 9.5# J-55 casing set at 1489'. 1489'. Cemented w/200 sacks Class "C" with 4% gel, 3# salt, 2% Ca .1% Halad-4. Compressive strength of cement - 1250 psi in 12 hour 10-18-82. Bumped plug to 1000 psi, released pressure and float he	aCl ₂ , .2% CFR-2, rs. PD 12:30 PM eld okay. Cement
TD 1500'. Ran 37 joints of 4-1/2" 9.5# J-55 casing set at 1489'. 1489'. Cemented w/200 sacks Class "C" with 4% gel, 3# salt, 2% Ca .1% Halad-4. Compressive strength of cement - 1250 psi in 12 hour 10-18-82. Bumped plug to 1000 psi, released pressure and float he	aCl ₂ , .2% CFR-2, rs. PD 12:30 PM eld okay. Cement
TD 1500'. Ran 37 joints of 4-1/2" 9.5# J-55 casing set at 1489'. 1489'. Cemented w/200 sacks Class "C" with 4% gel, 3# salt, 2% Ca .1% Halad-4. Compressive strength of cement - 1250 psi in 12 hour 10-18-82. Bumped plug to 1000 psi, released pressure and float he	aCl ₂ , .2% CFR-2, rs. PD 12:30 PM eld okay. Cement
TD 1500'. Ran 37 joints of 4-1/2" 9.5# J-55 casing set at 1489'. 1489'. Cemented w/200 sacks Class "C" with 4% gel, 3# salt, 2% Ca .1% Halad-4. Compressive strength of cement - 1250 psi in 12 hour 10-18-82. Bumped plug to 1000 psi, released pressure and float he	aCl ₂ , .2% CFR-2, rs. PD 12:30 PM eld okay. Cement
TD 1500'. Ran 37 joints of 4-1/2" 9.5# J-55 casing set at 1489'. 1489'. Cemented w/200 sacks Class "C" with 4% gel, 3# salt, 2% Ca .1% Halad-4. Compressive strength of cement - 1250 psi in 12 hour 10-18-82. Bumped plug to 1000 psi, released pressure and float he	aCl ₂ , .2% CFR-2, rs. PD 12:30 PM eld okay. Cement
TD 1500'. Ran 37 joints of 4-1/2" 9.5# J-55 casing set at 1489'. 1489'. Cemented w/200 sacks Class "C" with 4% gel, 3# salt, 2% Ca .1% Halad-4. Compressive strength of cement - 1250 psi in 12 hour 10-18-82. Bumped plug to 1000 psi, released pressure and float he	aCl ₂ , .2% CFR-2, rs. PD 12:30 PM eld okay. Cement
TD 1500'. Ran 37 joints of 4-1/2" 9.5# J-55 casing set at 1489'. 1489'. Cemented w/200 sacks Class "C" with 4% gel, 3# salt, 2% Ca .1% Halad-4. Compressive strength of cement - 1250 psi in 12 hour 10-18-82. Bumped plug to 1000 psi, released pressure and float he	aCl ₂ , .2% CFR-2, rs. PD 12:30 PM eld okay. Cement
TD 1500'. Ran 37 joints of 4-1/2" 9.5# J-55 casing set at 1489'. 1489'. Cemented w/200 sacks Class "C" with 4% gel, 3# salt, 2% Ca .1% Halad-4. Compressive strength of cement - 1250 psi in 12 hour 10-18-82. Bumped plug to 1000 psi, released pressure and float he circulated 15 sacks to pit. WOC 18 hours. Waiting on completion	aCl ₂ , .2% CFR-2, rs. PD 12:30 PM eld okay. Cement
TD 1500'. Ran 37 joints of 4-1/2" 9.5# J-55 casing set at 1489'. 1489'. Cemented w/200 sacks Class "C" with 4% gel, 3# salt, 2% Ca .1% Halad-4. Compressive strength of cement - 1250 psi in 12 hour 10-18-82. Bumped plug to 1000 psi, released pressure and float he	aCl ₂ , .2% CFR-2, rs. PD 12:30 PM eld okay. Cement
TD 1500'. Ran 37 joints of 4-1/2" 9.5# J-55 casing set at 1489'. 1489'. Cemented w/200 sacks Class "C" with 4% gel, 3# salt, 2% Ca .1% Halad-4. Compressive strength of cement - 1250 psi in 12 hour 10-18-82. Bumped plug to 1000 psi, released pressure and float he circulated 15 sacks to pit. WOC 18 hours. Waiting on completion	aCl ₂ , .2% CFR-2, rs. PD 12:30 PM eld okay. Cement unit.
TD 1500'. Ran 37 joints of 4-1/2" 9.5# J-55 casing set at 1489'. 1489'. Cemented w/200 sacks Class "C" with 4% gel, 3# salt, 2% Ca .1% Halad-4. Compressive strength of cement - 1250 psi in 12 hour 10-18-82. Bumped plug to 1000 psi, released pressure and float he circulated 15 sacks to pit. WOC 18 hours. Waiting on completion	aCl ₂ , .2% CFR-2, rs. PD 12:30 PM eld okay. Cement