

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well2. NAME OF OPERATOR
Yates Petroleum Corporation3. ADDRESS OF OPERATOR
207 South 4th St., Artesia, NM 882104. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1650 FNL & 1650 FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐
☐RECEIVED
SEP 30 1982

NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 14-3/4" hole at 1:15 PM 9-26-82. Ran 9 jts of 10-3/4" 40.5# J-55 ST&C casing set at 344'. 1-Texas Pattern notched guide shoe at 344'. Insert float at 303'. Cemented w/225 sacks Class "C", 1/4#/sack flocele and 3% CaCl₂. Compressive strength of cement - 1275 psi in 12 hours. PD 12:00 AM 9-27-82. Bumped plug to 750 psi, released pressure and float held okay. Cement circulated 35 sacks. WOC. Drilled out at 12:00 PM 9-27-82. WOC 12 hours. Cut off and welded on flow nipple. Reduced hole to 9-7/8". Drilled plug and resumed drilling. Ran 28 jts of 7" 23# J-55 LT&C casing set at 1144'. 1-Texas Pattern notched guide shoe at 1144'. Insert valve float at 1108'. Cemented w/300 sacks Pacesetter Lite, 5#/sack gilsonite and 3% CaCl₂. Tailed in w/150 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 1:30 AM 9-28-82. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 30 sacks. WOC. Drilled out 7:30 PM 9-29-82. Nippled up and tested to 1000 psi, OK. Reduced hole to 6-1/4". Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Michael D. Doherty TITLE Engineering Secty DATE 9-29-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF

APPROVAL, IF ANY:

OCT 4 1982

TITLE _____

DATE _____

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side