

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER 10  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Pet. Co.</u>		Lease <u>Eagle Creek BL</u>		Well # <u>3</u>	
Location of Well	Unit <u>N</u>	Section <u>23</u>	Township <u>17</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor	<u>L &amp; M #2</u>		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>14 1/2"</u>	<u>10 3/4"</u>	<u>30#</u>	<u>New</u>	<u>350'</u>	<u>Circ</u>
<u>9 1/2"</u>	<u>7"</u>	<u>23#</u>	<u>"</u>	<u>1150'</u>	<u>Circ</u>
<u>6 1/2"</u>	<u>4 1/2"</u>	<u>9.5#</u>	<u>"</u>	<u>1500</u>	<u>Circ</u>

Casing Data:

Surface        joints of        inch        # Grade         
(Approved) (Rejected)       

Inspected by        date       

Cementing Program

Size of hole        Size of Casing        Sacks cement required       

Type of Shoe used        Float collar used        Btm 3 jts welded       

TD of hole 111 Set 110 Feet of 7 Inch 12 # Grade       

New-used csg. @        with 150 sacks neat cement around shoe 2 1/2 #

+ 300 sax        additives       

Plug down @ 7:00 (AM) (PM) Date 11/2/82

Cement circulated NO No. of Sacks       

Cemented by        Witnessed by       

Temp. Survey ran @ 1:00 (AM) (PM) Date 11/10/82 top cement @ 455'

Casing test @        (AM) (PM) Date       

Method Used        Witnessed by       

Checked for shut off @        (AM) (PM) Date       

Method used        Witnessed by       

Remarks: Tagged @ 465' Lc @ 730' Pump 7500 22 1/2

Tagged @ 357 pumped 30 sacks 3% C. C.

Tagged @ 357' Pumped 100 sacks 3% C. C.

Circ. cement to the 14