

458

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Forister & Sweatt

3. ADDRESS OF OPERATOR

PO Box 161, Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660 FNI. 2130 FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT CF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) casing & cement ☐

5. LEASE

NM 15007

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Bear Draw Fred.

9. WELL NO.

4

10. FIELD OR WILDCAT NAME

Bear Draw Q.G.SA.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 28 T16S R29E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3634.8 Gr.

RECEIVED

(NOTE: Report results of multiple completion or zone changes on Form 9-330.)

DEC 6 1982

OIL & GAS

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drilled 12 1/4" hole 352'. Ran 9 jts 352' 8 5/8" 28# casing set at 350'. Cemented with 50 sacks Hal Thick set with 2% C clor. Followed with 200 sacks Class C with 2% Cal Clor. Circulated 25 sacks to pit. Plug down 9:20 p.m. 11/17/82.

2. Drilled 7 7/8" hole to 2650' - logged. Ran 66 jts 2679' 4 1/2" 9.5# casing set at 2650'. Cemented with 550 sacks Hal Light with 6# salt 1/4# Flocele per sack. Followed with 260 sacks 50/50 poz 6# salt and 3% CFR-2. Circulated 100 sacks to pit. Plug down 10:35 a.m. 11/23/82.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

David R. Glass

TITLE

Partner

DATE

12-2-82

APPROVED BY
CONDITIONS OF APPROVAL

(ORIG. SGD.) DAVID R. GLASS

TITLE

DATE

DEC 07 1982

MINERALS MANAGEMENT SERVICE

ROSWELL, NEW MEXICO

*See Instructions on Reverse Side