••. •• to-na sitema	ERVATION DI RECEIVED	
	CO. BOX 2088 RECEIVED	······································
	T. NEW MEXICO 87501	Form C-1 Revised
K K		
U.3.G.3.	MAR 0 8 1983	Su. Indicate Type of Lesse
LAND OFFICE		State Y Fo
Prenaro.	[°] O. C. D.	5. state Off & Gus Leave No.
	ARTESIA, OFFICE	E-3510
SUNDRY NOTICES AND REPORT	RTS ON WELLS	
OIL GAS X OTHER-		7. Unit Agreement Name
ame of Operator		8. Fam or Lease Name
Amoco Production Company 🗸		
Address of Operator		<u>State "MT" Com</u>
P. O. Box 68, Hobbs, New Mexico 88240		9. Well No.
ocation of well		1
1080 Se		10. Field and Pool, or wildest
UNIT LETTER I 1980 FEET FROM THE South LINE AND 660		Wildcat Morrow
THE East LINE, SECTION 1 TOWNSHIP	<u>-S</u>	
15. Eluvation (Show whether DF, RT, GR, etc.) 3683.2' GL		12. County ALLI
		Eddy
Check Appropriate Box To Ind	icate Nature of Notice Report	t of Other Dura
- NOTICE OF INTENTION TO:	SUBSE	QUENT REPORT OF:
PORM REMEDIAL WORK	DON REMEDIAL WORK	ALTURING CASING
PORAAILY AJANDON	COMMENCE ORILLING OPHS.	
L OR ALTER CASING CHANGE PLANS	CASING TEST AND CEMENT JOB	
	OTHER	
DTHER		
Descrite Proposed or Completed Operations (Clearly state all pert work) SEE RULE 1 fos.		

On 2-20-83, drilled to a total depth of 410'. Ran 13-3/8" 54.5#, J-55, and 48# H-40 casing and set at 410'. Cemented with 450 sx class C with 2% CACL. Plugged down with no circulation at any time. Ran 1" pipe and tagged cement at 180'. Cemented with 50 sx class "C" and wait on cement. Ran 1" pipe and tagged cement at 180'. Cemented with 25 sx class "C" with 3% CACL. WOC. Ran 1" pipe and tagged cement at 126'. Cemented with 25 sx class "C" with 3% CACL. WOC. Ran 1" pipe and tagged cement at 70'. Cemented with 25 sx class "C" with 3% CACL. WOC. Ran 1" pipe and tagged cement at 70'. Cemented with 75 sx class "C" with 3% CACL. WOC. Ran 1" and tagged cement at 70'. Cemented with 50 sx. Thixset. (Per Verbal approval Les Clement to Herring 2-21-83, 8:00 am). WOC. Ran 1" and tagged cement at 60'. Cemented with 50 sx Thixset. WOC. Ran 1" and tagged cement at 60'. Cemented with 135 sx class "C" with 3% CACL. Top of cement at 60'. Cemented with 4 CU yards Ready Mix and 3% CACL. (Per verbal approval Mike Williams to Herring). Cement at surface. WOC. Pressure test casing to 600 psi for 30 min.-OK. Reduced bit to 12-1/2" and resumed drilling. On 2-7-83, drilled to total depth of 2659'. Ran 8-5/8" 28# S-80 casing and set at 2659'. Cemented casing with 1150 sx class C lite with 15# per sx salt. Tail in 400 sx class "C" neat. Plugged down and circulated 563 sx cement. Pressure tested at 1000 psi for 30 min-OK. Reduced bit to 7-7/8" and resumed drilling.

Amore White black	OIL AND GAS INSPECTOR	MAR 0 9 1983
id. I hereby certy that the information above is true and complete alcaro Harby Tr. & Drung		

CONDITIONS OF APPROVAL, IF ANY: