

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
Artesia NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE 1650 FNL & 990 FWL, Sec. 27-17S-25E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) ☐

SUBSEQUENT REPORT OF:

☒☐☐☐☐☐☐☐☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 14-3/4" hole 8:30 AM 12-6-82. Ran 9 jts of 10-3/4" 40.5# K-55 ST&C casing set at 361'. 1-Texas Pattern notched guide shoe set at 361'. Insert float set at 323'. Cemented w/225 sacks Class "C" 3% CaCl₂. Compressive strength of cement - 1250 psi in 12 hrs. PD 5:00 PM 12-6-82. Bumped plug to 1000 psi for 30 minutes, okay. Drilled out 5:30 AM 12-7-82. WOC 12 hours and 30 minutes. Cut off and welded on flow nipple. Reduced hole to 9-7/8". Drilled plug and resumed drilling. Ran 30 jts of 7" 23# K-55 LT&C casing set at 1190'. 1-Texas Pattern notched guide shoe set at 1190'. Insert float at 1150'. Cemented w/375 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hrs. PD 9:15 PM 12-7-82. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 30 sacks. Drilled out 3:15 PM 12-8-82. WOC 18 hrs. Nippled up and tested to 1000 psi for 30 minutes, okay. Reduced hole to 6-1/4". Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct
ProductionSIGNED David R. Glass TITLE Supervisor DATE 12-13-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY (ORIG. SGD.) DAVID R. GLASS

CONDITIONS OF APPROVAL: NONE

DATE

DEC 16 1982

MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

5. LEASE

NM 0630

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal LDY

9. WELL NO.

5

10. FIELD OR WILDCAT NAME

Eagle Creek SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit E, Sec. 27-T17S-R25E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3540' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330)

OIL & GAS
MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO