

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRI-CATEGORY
Other instructions on reverse side.

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.
NM 0439900

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal CB Com

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Undes. Eagle Creek Strawn

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit N, Sec. 15-17S-25E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER RECOMPLETION

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

105 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.
At surface

660' FWL & 1980' FWL, Sec. 15-T17S-R25E

14. PERMIT NO.

API #30-015-24370

15. ELEVATIONS (Show whether DE, RT, GK, etc.)

3530' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Change zones, perforate, trt

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

5-11-89. MIRU for recompletion.

5-21-89. Found hole in casing about 5665'.

5-23-89. WIH w/retainer and set 5511'. Cemented w/750 sx Class C w/silicalite blend and 150 sx Class C with salt, Flocele and Halad-4.

5-25-89. Drilled out retainer at 5511'.

6-3 - 6-5-89. Swabbed Atoka. Recovered 4 bbls distillate muddy water with 2' flare.

6-6-89. Perforated Strawn 7617-7621' w/8 .41" holes (2 SPF), 7623-7625' w/4 .41" holes (2 SPF), total 12 holes.

6-7-89. Set RBP 7644' and tested to 2700 psi. Treated perms 7617-7625' w/1000 gals 7½% Spearhead acid.

6-9-89. Well flowed 225 psi on 1/4" choke = 350 mcf/gpd.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Production Supervisor

DATE 6-14-89

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

SJS