

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>YATES PET. CO</u>		Lease <u>JACKSON AT</u>		Well # <u>17</u>	
Location of Well	Unit <u>M</u>	Section <u>13</u>	Township <u>15</u>	Range <u>25E</u>	County <u>EDDY</u>
Drilling Contractor	<u>AET #1</u>		Type of Equipment <u>ROTARY</u>		
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>14 1/2"</u>	<u>10 3/4"</u>	<u>32#</u>	<u>NEW</u>	<u>340</u>	<u>CIRC</u>
* <u>7 1/2"</u>	<u>7"</u>	<u>23#</u>	<u>"</u>	<u>1190'</u>	<u>CIRC</u>
<u>6 1/4"</u>	<u>4 1/2"</u>	<u>9.5#</u>	<u>"</u>	<u>"</u>	<u>CIRC</u>
Casing Data:					
Surface _____ joints of _____ inch _____ # Grade _____					
(Approved) (Rejected) _____					
Inspected by _____ date _____					
Cementing Program					
Size of hole <u>9 7/8</u> Size of Casing <u>7</u> Sacks cement required _____					
Type of Shoe used <u>RY-B</u> Float collar used <u>Insert</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>1200</u> Set <u>1203</u> Feet of <u>7</u> Inch <u>23</u> # Grade <u>J-55</u>					
New used csg. @ <u>1203</u> with <u>175</u> sacks neat cement around shoe					
+ <u>250</u> sax <u>Pace Setter lite</u> additives <u>1/4 Flo Sol #10 Silicate 3% CC</u>					
Plug down @ <u>845</u> (AM) (PM) Date <u>3-9-83</u>					
Cement circulated <u>yes</u> No. of Sacks <u>40</u>					
Cemented by <u>Western</u> Witnessed by <u>Bill Weaver</u>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: <u>Last Drilling Break 1096 Loss zone @ 740</u>					