NM OIL CONS. COMMI Drawer DD	ISSION C/OM
Form 9-331 Diawer 10. Dec. 1973 Artesia, MU 838310	Form Approved.
UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE NM-0630
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME RECEIVED 8. FARM OR LEASE NAME APR 0.4 1002
1. oil et gas (8. FARM OR LEASE NAME APR 0 4 1983
 well L3 well L1 other 2. NAME OF OPERATOR Yates Petroleum Corporation 3. ADDRESS OF OPERATOR 207 S. 4th St., Artesia, NM 88210 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1650' FNL & 1650' FWL AT TOP PROD. INTERVAL: 	9. WELL NO. 7 ARTESIA, OFFICE 10. FIELD OR WILDCAT NAME Eagle Creek (SA) 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit F Sec. 27-T17S-R25E 12. COUNTY OR PARISH 13. STATE Eddy NM
AT TOTAL DEPTH:	14. API NO.
 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3539' GL
TEST WATER SHUT-OFF Image: Subsequent Report of the subsequence re	(NOTE: Report results of multiple comparing zone Marine and Solo 1983)
(other)	<u>^</u>
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is di measured and true vertical depths for all markers and zones pertinen	rectionally drilled, give subsurface locations and
Spudded 14-3/4" hole 2:45 pm 3-26-83. Ran 9 jot casing set 342'. 1-Texas Pattern notched guide set 302'. Cemented with 225 sacks Class "C" 3% coment - 1275 psi in 12 hours. PD 9:00 pm 3-26- released pressure and float held okay. Cement of Drilled out 9:15 am 3-27-83. WOC 12 hours and 1 on flow nipple. Reduced hole to 9-7/8". Drilled	shoe set 342'. Insert float CaCl ₂ . Compressive strength of -83. Bumped plug to 1000 psi, circulated 30 sacks. WOC. 15 minutes. Cut off and welded

Subsurface Safety Valve: Manu. and Type	Set @	Ft.
18. Thereby certify that the pregoing is true and correct		
SIGNER Lands and and allet TITLE Production Supervisor	3-29-83	
ACCEPTED FOR RECORD (ORIG. SGD.) DAVID R. GLASS		
(ORIG. SGD.) DAVID K. GLANN		
(ORIG. SGD.) DAVID R. GLAND APPROVED BY CONDITIONS OF APPROVMAR ON 1983		
MINERALS MANAGEMENT SERVICE ROSWELL, NEW MEXICO		
*See Instructions on Reverse Side		