

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

RECEIVED L.
OCT 11 1983
O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-78

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - D" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

1. Name of Operator
Yates Petroleum Corporation

2. Address of Operator
207 South 4th St., Artesia, NM 88210

3. Location of Well
UNIT LETTER I 2310 FEET FROM THE South LINE AND 330 FEET FROM
THE East LINE, SECTION 14 TOWNSHIP 17S RANGE 25E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3469' GR

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>	
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name Achen Frey DM	
9. Well No. 11	
10. Field and Pool, or Wildcat Eagle Creek SA	
12. County Eddy	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPS. ☒
CASING TEST AND CEMENT JOBS ☒
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
OTHER ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 14-3/4" hole 11:30 AM 10-3-83. Set 40' of 20" conductor. Ran 8 joints of 10-3/4" of casing set 347'. 1-Texas Pattern notched guide shoe set 347'. Insert float set 304'. Cemented w/225 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 4:30 PM 10-3-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement did not circulate. Filled with Ready Mix. WOC. Drilled out 4:30 AM 10-4-83. WOC 12 hours. Cut off and welded on flow nipple. Reduced hole to 9-7/8". Drilled plug and resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature]

TITLE Production Supervisor

DATE 10-5-83

APPROVED BY [Signature]

TITLE OIL AND GAS INSPECTOR

DATE OCT 14 1983

CONDITIONS OF APPROVAL, IF ANY: