

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator YATES PET. CO		Lease GISSLER AV		Well # 36	
Location of Well	Unit L	Section 23	Township 17S	Range 25E	County EDDY
Drilling Contractor	LARUE #2		Type of Equipment RDARY		
* Witness APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
14 1/2"	10 3/4"	32#	NEW	320'	LIRC
* 9 1/2"	7"	23#	"	1150'	"
6 1/4"	4 1/2"	9.5	"	TD	"
Casing Data:					
Surface 29 joints of 7 inch 23 # Grade J-55					
(Approved) (Rejected)					
Inspected by B.W. Weaver date					
Cementing Program					
Size of hole 9 7/8 Size of Casing 7 Sacks cement required 150					
Type of Shoe used Tex-Pat Float collar used Insert Btm 3 jts welded Yes					
TD of hole 1152 Set 1154 Feet of 7 Inch 23 # Grade J-55					
New-csg. @ 1154 with 150 sacks neat cement around shoe					
+ 150 sax Pace Setter lfe additives 1/4 Flo-Sol, #5 Gilsonite, 3% Calcium Chloride					
Plug down @ 4:15 (AM) (PM) Date 9-10-83					
Cement circulated No No. of Sacks					
Cemented by Wastern Witnessed by B.W. Weaver					
Temp. Survey ran @ 10:00 (AM) (PM) Date 9-10-83 top cement @ 730					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ (AM) (PM) Date					
Method used Witnessed by					
Remarks: Loss Circulation @ 744 Last Drilling Break 1046					
Ran 1" to 680					
100 SX C 3% CC					
Tag @ 560					
50 SX C 3%					
Tag 430					
50 SX C 3% CC					
Tag @ 340					
50 SX C 3% CC					
Tag @ 156					
50 SX C 3% Circulated Cement					