				15
Form 3160-5 (June 1990)	UNITED ST DEPARTMENT OF T BUREAU OF LAND M	HE INTERIOR IANAGEMENT		Budget Bureau No. 1004-0135 10-2834 xpires: March 31, 1993 5. Lease Designation and Serial No. NMO439900
Do not use this for	SUNDRY NOTICES AND R n for proposals to drill or to a "APPLICATION FOR PERM	deepen or reentry to	a different reservoir.	6. If Indian, Allottee or Tribe Name
	SUBMIT IN TRI		<u>k</u>	7. If Unit or CA, Agreement Designation
I. Type of Well Oil Gas   Well Well Well   2. Name of Operator WELL			SECENTED IN	8. Well Name and No. Federal CB #4
YATES PETROLEUM CORPORATION   (505) 748-14719 ARTESTA     3. Address and Telephone No.   000				9. API Well No. 30-015-24555 10. Field and Pool, or Exploratory Area
105 South 4th St., Artesia, NM 88210 4 Location of Well (Footage, Sec., T., R., M., or Survey Description) 330' FSL & 1650' FEL of Section 15-T17S-R25E (Unit O, SWSE)				10. Field and Pool, or Exploratory Area <u>Eagle Creek San Andres</u> 11. County or Parish, State
				Eddy Co., NM
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR				RT, OR OTHER DATA
TYPE OF S	UBMISSION		TYPE OF ACTION	
Notice of	1	X Abandonment Recompletion		Change of Plans Post ID- New Construction 3-6-98
X Subsequer		Plugging Back Casing Repair Altering Casing		Water Shut-Off <b>PYA</b> Conversion to Injection
	ndonment Notice	Other		Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and 1 og form.)
give subsurface locat 1-20-98 - Mor- and pump. B answering ma 1-21-98 - Ni seating nipp with mud lad POOH with tu 1-22-98 - Op hole with mu set another 870'. Spott 15 sacks Cla	wed in and rigged up p led down 2-3/8" X 4-1/ chine of commencing op ppled down wellhead. le and mud anchor. The en fluid. Could not b bing. WOC. Shut well ened up well. TIH with d laden fluid. NOTE: plug. Spotted 15 sach ed 15 sacks Class C co ss C cement from 400-1 m 144' to surface. Po gulation abandonment f	oulling unit. N 2" annulus. Sh perations. Nippled up BOP. H with tubing. Load hole. Spot L in. NOTE: No th tubing. Tagg Consulted with cs Class C cement ement from 870-6 183'. POOH with	POOH with 43 j Nixed mud. Att ted 15 sacks Cla otified Jim Amos ged top of cement Jim Amos w/BLM- nt from 1312-1095 553'. POOH with h tubing to 144'. Nippled down F	oints of tubing (2-3/8"), cempted to circulate hole ass C 2% CaCl2 at 1480'.
the back of the second	foregoing is true and correct			
Signed		TileOperation	ns Technician	Date Jan. 26, 1998
(This serve for Federal	PIG. SGD.) GARY GOURLE	Tille PETROL	EUM ENGINEER	FEB 0 3 1998
Conditions of approval,	if any:	•••• قتب ا		-

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



RECEIVED



•