

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Drawer DD
Artesia, NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐
well well other

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2310 FNL & 330 FWL, Sec. 27-17S-25E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐

5. LEASE

NM 0630

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federal LDY

9. WELL NO.

9

10. FIELD OR WILDCAT NAME
Eagle Creek SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit E, Sec. 27-T17S-R25E

12. COUNTY OR PARISH
Eddy

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3545' GR

(NOTE: Report results of multiple completions or zone change on Form 9-330C)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 14-3/4" hole 6:00 PM 8-21-83. Set 30' of 20" conductor pipe. Ran 8 joints 10-3/4" 40.5# J-55 casing set 322'. 1-Texas Pattern notched guide shoe set 322'. Insert float set 279'. Cemented w/225 sacks Class "C" 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hours. PD 12:45 AM 8-22-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Drilled out 1:00 PM 8-22-83. WOC 12 hours and 15 minutes. Cut off and welded on flow nipple. Reduced hole to 9-7/8". Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

Production

SIGNED [Signature] TITLE Supervisor

DATE 8-23-83

(This space for Federal or State office use)

APPROVED BY TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

AUG 26 1983

*See Instructions on Reverse Side

ROSWELL, NEW MEXICO