

c/sf

OIL CONS. COMMISSION  
Drawer DD  
Artesia, NM 88210

Form 9-331  
Dec. 1973

RECEIVED

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

6-26 2 47 PM '83

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) Unit J

AT SURFACE: 1980' FE & SL  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

5. LEASE

NM - 18973

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Five Forks Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat -

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 15, T 17S, R 27E, NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3490 Ground

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8/30/83 MI and RU Yucca Drlg. Set 25' of 8-5/8" K-55 Casing in 12-1/4" hole. Cemented to surface w/ 30 sx. of Ready Mix Concrete.  
8/31/83 Yucca Drlg. started drlg 7-7/8" hole.  
9/1/83 Finished drilling at 761'. RU Geosource Wireline and ran Radioactivity/Gamma log.  
9/2/83 Finished logging operations. Dry hole. Denton Cementing plugged well with 35 sx Class C Cement at 100' to surface. RD and released Yucca Drlg. on 9/2/83.

Post ID-2  
8-1-86  
P+A

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Daniel S. Bohrer TITLE Petroleum Engineer DATE 9/22/83

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: