

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>C E L. R. &amp; B. M. Murrey Jr</u>			Lease <u>State M</u>		Well # <u>1</u>
Location of Well	Unit <u>m</u>	Section <u>36</u>	Township <u>17</u>	Range <u>27</u>	County <u>Eddy</u>
Drilling Contractor	<u>Artesia Fishing Tool #1</u>		Type of Equipment <u>Rotary</u>		

\* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
* <u>11 1/4</u>	<u>8 5/8</u>	<u>24 #</u>		<u>275'</u>	<u>Circ</u>
* <u>7 7/8</u>	<u>4 1/2</u>	<u>9 1/2 #</u>		<u>1460'</u>	<u>Circ</u>

Casing Data:

Surface 7 joints of 8 5/8 inch 24 # Grade J-55  
yes (Approved) (Rejected)

Inspected by BW Weaver date \_\_\_\_\_

Cementing Program

Size of hole 11 1/4 Size of Casing 8 5/8 Sacks cement required \_\_\_\_\_

Type of Shoe used Ter. Pat Float collar used Insert Btm 3 jts welded yes

TD of hole 281 Set 292 Feet of 8 5/8 Inch 24 # Grade J-55

New-used csg. @ 292 with 200 sacks neat cement around shoe  
 + \_\_\_\_\_ sacks additives \_\_\_\_\_

Plug down @ 915 (AM) (PM) Date 9-30-13

Cement circulated yes No. of Sacks 40

Cemented by Hawco Witnessed by BW Weaver

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: \_\_\_\_\_