

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other _____
2. NAME OF OPERATOR
Yates Petroleum Corporation
3. ADDRESS OF OPERATOR
207 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1650 FSL & 2310 FWL
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
PULL OR ALTER CASING
MULTIPLE COMPLETE
CHANGE ZONES
ABANDON*
(other)

X

5. LEASE
NM 12832
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Federal CD
9. WELL NO.
4
10. FIELD OR WILDCAT NAME
Eagle Creek SA
11. SEC., T., R., M., OR BLK. AND SURVEY OR
AREA
Unit K, Sec. 29-T17S-R25E
12. COUNTY OR PARISH
Eddy
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KOB. AND WD)
3604' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 14-3/4" hole 3:15 PM 11-14-83. Ran 8 jts 10-3/4" 40.5# J-55 casing set 333'. 1-Texas Pattern notched guide shoe set 333'. Insert float set 291'. Cemented w/ 225 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 10:15 PM 11-14-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 5 sacks to pit. WOC. Drilled out 12:30 PM 11-15-83. WOC 14 hours and 15 minutes. Cut off and welded on flow nipple. Tested casing to 1000 psi for 30 minutes, OK. Reduced hole to 9-7/8". Drilled plug and resumed drilling. Note: Lost returns 682'

Subsurface Safety Valve: Manu. and Type Set @ Ft.

- 18.** I hereby certify that the foregoing is true and correct

18. I hereby certify that the foregoing is true and correct.

SIGNED [Signature] TITLE Production Supervisor DATE 11-16-83

~~ACCEPTED FOR RECORD~~

space for Federal or State office use)

APPROVED BY (ORIG. SGD.) DAVID R. GLASS
CONDITIONS OF APPROVAL: 140799Z 1983

DATE _____

ROSWELL, NEW MEXICO

*See Instructions on Reverse Side