

NM OIL CONS. COMMISSION
Drawer DD
Artesia, NM 88210
UNITED STATES

Form Approved.
Budget Bureau No. 42-R1424

AMENDED*

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well ☒ gas well ☐ other

2. NAME OF OPERATOR
Yates Petroleum Corporation

3. ADDRESS OF OPERATOR
207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 330 FNL & 990 FEL, Sec. 31-17S-25E
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

(other) Production Casing, Perforate, Treat

5. LEASE

NM 15664

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal EF

9. WELL NO.

3

10. FIELD OR WILDCAT NAME

Eagle Creek SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit A, Sec. 31-T17S-R25E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3617' GR

RECEIVED BY

DEC 13 1983

O. C. D.

ARTESIA, NM

(NOTE: Report results of multiple completions or zone change on Form 9-330.)

ROSWELL DISTRICT

DEC 9 9 28 AM 1983

RECEIVED

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 1400'. Ran 34 jts 4-1/2" 9.5# J-55 ST&C casing set 1400'. Float shoe set 1400'. Cemented w/175 sacks 1:2 Talc, 4% CF-2, .2% TF-4, .2% AF-S, 1% CaCl2. Compressive strength of cement - 950 psi in 12 hrs. PD 1:00 PM 11-7-83. Bumped plug to 1000 psi for 30 minutes, released pressure, float held okay. WOC 18 hrs. WIH and perforated 1103-1369' w/14 .42" holes as follows: 1103, 21, 56, 62, 95, 1209, 21 1/2, 33, 39, 48, 62, 96, 1321, and 69'. Perforated 1087-1293' w/16 .42" holes as follows: 1087, 1104 1/2, 26, 38, 46, 58, 66, 90, 1204, 24, 36, 42, 50 1/2, 57, 75 and 93'. Acidized perfs w/2500 gallons 20% NEFE acid and 5 ball sealers. Sand frac perfs (via casing) w/60000 gallons gelled KCL water, *100000# (90000# 20/40 and 10000# 100 Mesh) sand.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED David R. Glass TITLE Production Supervisor DATE 12-8-83

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY (ORIG. SGD.) DAVID R. GLASS TITLE _____ DATE _____
CONDITIONS OF APPROVAL: DEC 1 1983

ROSWELL, NEW MEXICO

*See Instructions on Reverse Side