

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIRECTOR
P. O. BOX 2081
SANTA FE, NEW MEXICORECEIVED BY
DEC 14 1983
O. C. D.
ARTESIA, OFFICEForm C-103
Revised 10-1-73

5. Indicate Type of Lease
State ☐ Fee ☒
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-10) FOR SUCH PROPOSALS.)

OIL WELL ☐	GAS WELL ☐	OTHER- Injection Well
Name of Operator Yates Petroleum Corporation ✓		
Address of Operator 207 South 4th St., Artesia, NM 88210		
Location of Well UNIT LETTER F 2055 FEET FROM THE North LINE AND 1330 FEET FROM West LINE SECTION 23 TOWNSHIP 17S RANGE 25E		

7. Unit Agreement Name
8. Farm or Lease Name Gissler AV
9. Well No. 39
10. Field and Pool, or Wildcat Eagle Creek SA
11. Elevation (Show whether DF, RT, GR, etc.) 3508' GR
12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
REEL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER Intermediate Casing ☒

1. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 27 jts 9-5/8" 36# J-55 casing set 1128'. 1-Texas Pattern notched guide shoe set 1128'. Regular guide shoe set 1091'. Cemented w/300 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hrs. PD 11:15 PM 11-9-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement did not circulate. WOC 6 hrs. Ran Temperature Survey and found top of cement - 760'. Ran 1". Tagged cement 471'. Spotted 75 sacks Class C 4% CaCl₂. PD 9:15 AM 12-10-83. WOC 2 hrs. Ran 1". Tagged cement 347'. Spotted 25 sacks Class C 4% CaCl₂. WOC 2 hrs. Ran 1". Tagged cement 337'. Spotted 35 sacks Class C 4% CaCl₂. PD 1:35 PM 12-10-83. WOC 2 hrs. Ran 1". Tagged cement 337'. Spotted 35 sacks Class C 4% CaCl₂. PD 3:35 PM 12-10-83. WOC 2 hrs. Ran 1". Tagged cement 331'. Spotted 35 sacks Class C 4% CaCl₂. PD 6:30 PM 12-10-83. WOC 2 hrs. Ran 1". Tagged cement 240'. Spotted 60 sacks Class C 4% CaCl₂. PD 9:00 PM 12-10-83. Cement circulated 10 sacks. WOC. Drilled out 12:00 noon 12-11-83. WOC 35 hrs and 45 minutes. NU and tested to 1000# for 30 minutes, OK. Reduced hole to 8-3/4". Drilled plug and resumed drilling.

I, I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>[Signature]</u>	TITLE <u>Production Supervisor</u>	DATE <u>12-13-83</u>
APPROVED BY <u>[Signature]</u>	TITLE <u>OIL AND GAS ENGINEER</u>	DATE <u>DEC 15 1983</u>
CONDITIONS OF APPROVAL, IF ANY:		