

OIL CONSERVATION DIVISION


P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-77

COPIES RECEIVED	
DISTRIBUTION	
SAMPLES	✓
FILE	✓
U.S.	
OFFICE	
ATION	✓

AMENDED REPORT*



5a. Indicate Type of Lease	State ☐ Fee ☒
5. State Oil & Gas Lease No.	
6. Unit Agreement Name	
8. Name of Lease Name	Gissler AV
9. Well No.	39
10. Field and Pool, or Wildcat	Eagle Creek SA
12. County	Eddy

SUNDARY NOTICES AND REPORTS ON WELLS
(DO NOT FILE THIS FORM FOR PROPOSED OR COMPLETED DRILLING OR PLUGGING OPERATIONS. USE APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☐ OTHER ☒ Injection Well.

Name of Operator
Yates Petroleum Corporation ✓

Address of Operator
207 South 4th St., Artesia, NM 88210

Location of Well
UNIT LETTER F 2055 FEET FROM THE North LINE AND 1330 FEET FROM THE West LINE, SECTION 23 TOWNSHIP 17S RANGE 25E NMPM.

15. Elevation (Show whether DI, RT, GR, etc.)
3508' GRCheck Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	Intermediate Casing ☒

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 27 jts 9-5/8" 36# J-55 casing set 1128'. 1-Texas Pattern notched guide shoe set 1128'. Regular guide shoe set 1091'. Cemented w/300 sacks Class "C" 2% CaCl₂. Tailed in w/200* sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hrs. PD 11:15 PM 11-9-83. Bumped plug to 1000 psi, released pressure and float held OK. Cement did not circulate. WOC 6 hrs. Ran Temperature Survey and found top of cement - 760'. Ran 1". Tagged cement 471'. Spotted 75 sacks Class C 4% CaCl₂. PD 9:15 AM 12-10-83. WOC 2 hrs. Ran 1". Tagged cement 347'. Spotted 25 sacks Class C 4% CaCl₂. WOC 2 hrs. Ran 1". Tagged cement 337'. Spotted 35 sacks Class C 4% CaCl₂. PD 1:35 PM 12-10-83. WOC 2 hrs. Ran 1". Tagged cement 337'. Spotted 35 sacks Class C 4% CaCl₂. PD 3:35 PM 12-10-83. WOC 2 hrs. Ran 1". Tagged cement 331'. Spotted 35 sacks Class C 4% CaCl₂. PD 6:30 PM 12-10-83. WOC 2 hrs. Ran 1". Tagged cement 240'. Spotted 60 sacks Class C 4% CaCl₂. PD 9:00 PM 12-10-83. Cement circulated 10 sacks. WOC. Drilled out 12:00 noon 12-11-83. WOC 35 hrs and 45 min. NU and tested to 1000# for 30 minutes, OK. Reduced hole to 8-3/4". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Production Supervisor DATE 1-27-84APPROVED BY _____ TITLE OIL AND GAS INSPECTOR DATE FEB 07 1984

CONDITIONS OF APPROVAL, IF ANY: