

RECEIVED BY

DEC 22 1983

O. C. D.
ARTESIA, OFFICEInjection Well - Approved Case #7035,
Order #7354

Yates Petroleum Corporation ✓

207 South 4th St., Artesia, NM 88210

K 2630

South 1980

West

23

17S

25E

3503' GR

Check appropriate box to indicate nature of logging operation or other data

NOTICE OF INTENTION TO:

PRODUCE OR REPRODUCE FOR:

PERFORM LOGGING WORK

PLUG AND ABANDON

REPAIR WORK

ALTERED LOGS

VERIFY RESULTS OF LOG

CHANGE PLUG

CONDUCT LOGGING OPERATIONS

RE-LOGGING OPERATIONS

VERIFY LOGGING SYSTEM

CIRCUIT LOGGING OPERATIONS

OTHER Production Logging, Perforate, Acidize (X)

I, the undersigned, hereby certify that the information above is true and complete to the best of my knowledge and belief.

TD 1500'. Run 38 joints of 5-1/2" 17# K-55 casing set 1500' 1-Float shoe set 1500'. Cemented w/375 sacks Class "C" .6% CF-1, 5#/sack salt, .2% AF-3. Compressive strength of cement - 950 psi in 12 hrs. PD 8:45 AM 12-6-83. Bumped plug to 1000 psi for 30 minutes, released pressure, float and casing held okay. Cement circulated 20 sacks to pit. WOC 18 hours. WOC and perforated 1301-1413' w/17 42" holes as follows: 1301, 21, 26, 31, 1339, 43, 47, 53, 59, 69, 73, 86, 94, 97, 1404, 08 and 13'. Acidized perforations w/1500 gallons 15% acid.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

TITLE Production Supervisor

DATE 12-19-83

OIL AND GAS INSPECTOR

TITLE

DATE

DEC 29 1983