

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESTA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

| | | | | | |
|---------------------|-----------|---------------------|-----------------------------|--------------|----------------|
| Operator YPC | | Lease GISSLER AV | | Well # 42 | |
| Location of Well | Unit L | Section 23 | Township 17 | Range 25 | County EDDY |
| Drilling Contractor | N/A | | Type of Equipment ROTARY | | |

* Witness

APPROVED CASING PROGRAM

| Size of Hole | Size of Casing | Weight Per Foot | New or Used | Depth | Sacks Cement |
|--------------|----------------|-----------------|-------------|-------|--------------|
| 17 1/2" | 13 3/8" | 48 # | NEW | 320' | CIRC |
| * 12 1/4" | 9 5/8" | 36 # | " | 1170' | " |
| 8 3/4" | 5 1/2" | 17 # | " | 1500' | " |

Casing Data:

Surface 27 joints of 9 5/8 inch 36 # Grade K-55

yes (Approved) (Rejected)

Inspected by B.W. Weaver date 12-21-83

Cementing Program

Size of hole 12 1/4 Size of Casing 9 5/8 Sacks cement required 200

Type of Shoe used Tex-Rot Float collar used Insert Btm 3 jts welded yes

TD of hole 1153 Set 1171 Feet of 9 5/8 Inch 36 # Grade K-55

New-used csg. @ 1171 with 200 sacks neat cement around shoe

+ 300 sax Pace Setter life additives

Plug down @ 1:00 (AM) (PM) Date 12-22-83

Cement circulated NO No. of Sacks

Cemented by Western Witnessed by BW Weaver

Temp. Survey ran @ 7:00 (AM) (PM) Date 12-22-83 top cement @ 520

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks:

Ran 1" to 464 Ran 100 SX C 4 1/2 CC

Tag @ 384 Ran 35 SX C 4 1/2 CC

Tag @ 384 Ran 35 SX C 4 1/2 CC

Tag @ 384 Ran 25 SX C 4 1/2 CC

Tag @ 384 Ran 30 SX C 4 1/2 CC

Tag @ 352 Ran 35 SX C 4 1/2 CC

Tag @ 352 Ran 30 SX C 4 1/2 CC

Tag @ 314 Ran 30 SX C 4 1/2 CC

Tag @ 124 Ran 75 SX C Circulate Cement to Surface