

RECEIVED BY

SEP 12 1984

UNITED STATES
DEPARTMENT OF THE INTERIOR
ARTESIA, OFFICE OF GEOLOGICAL SURVEY

NM OIL CONS. DIST.

Drawer DD

Artesia, NM 88210

75F

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Anadarko Production Company

3. ADDRESS OF OPERATOR

P. O. Drawer 130, Artesia, New Mexico 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FSL & 330' FWL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) Completion ☒☐☒☒☐☐☐☐☐☒

5. LEASE

NM - 081277

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

H. J. Loe Federal

9. WELL NO.

5

10. FIELD OR WILDCAT NAME

Square Lake-Grayburg-SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

31 - 16S - 31E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3807.6' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Rigged up pulling unit.
2. WIH with bit and drilled out cement retainer, cement and DV tool. Cleaned out to a PBTD of 3330'.
3. Ran GR/CCL log from 3330' to 2800'. Perforated Grayburg formation from 3025-3028 (4 holes), 3064-68 (5 holes) and 3104-08 (5 holes); total = 14 holes with .41" diameter.
4. Acidized with 1500 gals 15% NE-FE acid.
5. Fraced with 30,000 gals gel, 35,000# 20/40 sand & 42,770# 10/20 sand.
6. Flowed back and washed out sand.
7. WIH with tubing, rods and bottomhole pump.
8. Installed pumping equipment and placed well on production.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Thurman D. Jones TITLE Field Foreman DATE Sept. 6, 1984

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

SEP 11 1984

Carlsbad,

NEW MEXICO

*See Instructions on Reverse Side