NEW MEXICO OIL CONSERVATION COMMISSION DRAWER DD ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Sept 1-13-75

| Operator YPC | | | Lease | Lease KEPPEL | | ZN | Well # | , |
|--|-----------|----------------|-------|--------------------|--|--------------------|----------------|-------------|
| Location of Well | Unit • | Section 18 | | Townsh | | Range 27 | County Eddy | |
| Drilling Contractor Landis #4 Type of Equipment Retary | | | | | | | , | |
| * = CSG. TO WITNESS | | | | | | | | |
| APPROVED CASING PROGRAM | | | | | | | | |
| Size of Hole | Size | Size of Casing | | Weight Per Foot | | or Used | Depth | Sacks Cemen |
| וקו | 1 | 133/8" | | 48# | | Vew | 400 | Circ |
| ¥ 12/4" | | 85/8" | | 24 [#] | | 11 . | 1320 | Circ |
| 77/8" | 51/2 | 51/2 or 41/2 | | 17.5 or 9.5 | | 11 | TD | 250 5X |
| Casing Data: | | | | | | | | |
| Surface joints of inch # Grade | | | | | | | | |
| | | | | | | | | |
| (Approved) (Rejected) date | | | | | | | | |
| | | | | | | | | |
| Cementing Program | | | | | | | | |
| Size of hole 12/4 Size of Casing 8578 Sacks coment required 500 | | | | | | | | |
| Type of Shoe used Wherefloat collar used inst Btm 3 jts welded Yes | | | | | | | | |
| TD of hole 1335 Set 1342 Feet of 8% Inch 24 # Grade J-55 | | | | | | | | |
| New used csg. @ 1335 with 200 sacks near cement around shoe c. C 2% (all + 300 sax PACESETTER LITE additives 3% Call 200 | | | | | | | | |
| Plug down @ 5:30 (AM) (PM) Date 7/25 | | | | | | | | |
| Cement circulated Wes Yes No. of Sacks 40 | | | | | | | | |
| Cemented by WESTERN Witnessed by January | | | | | | | | |
| Temp. Survey ran @ (AM) (PM) Date top cement @ | | | | | | | | |
| Casing test @ (AM) (PM) Date | | | | | | | | |
| Method Used Witnessed by | | | | | | | | |
| Checked for shut off @ (AM) (PM) Date | | | | | | | | |
| Method used Witnessed by | | | | | | | | |
| Remarks: | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | • | |