

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instruct or re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

4/5F

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

| | | | |
|--|--|---|--|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | | RECEIVED BY AUG 08 1984 | |
| 2. NAME OF OPERATOR Fred F. Pool, III 622-4818 | | O. C. D. ARTESIA, OFFICE | |
| 3. ADDRESS OF OPERATOR 5 Summer Wind Place, Roswell, NM 88201 | | 5. LEASE DESIGNATION AND SERIAL NO. NM-54425 | |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1880' FSL & 1830' FWL | | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME | |
| 14. PERMIT NO. | | 7. UNIT AGREEMENT NAME | |
| 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4,085 GR | | 8. FARM OR LEASE NAME Ronadero 9 USA | |
| | | 9. WELL NO. #1 | |
| | | 10. FIELD AND POOL, OR WILDCAT Square Lake #7, Grby/S.A. | |
| | | 11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA Section 9, T16S, R31E | |
| | | 12. COUNTY OR PARISH Eddy | |
| | | 13. STATE NM | |

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐

REPAIRING WELL

☐
☐
☐

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Casing & Cement Job

☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-3-84 T.D. 3740'. Ran 3740' (90 jts.) of 5 1/2", 15.5#, API, LT & C casing, with regular guide shoe and float collar. Cemented with 750 sx HOWCO "LITE" with 15# salt and 1/4# FLOCELE, and tailed in with 600 sx class "H", with .6# salt and 3/10 of 1% CFR-2. Circulated 140 sx to surface. Plug down at 1:45 p.m.

I hereby certify that the foregoing is true and correct

SIGNED

Fred F. Pool, III

TITLE Operator

DATE 8-4-84

(This space for Federal or State office use)

APPROVED BY

SWQ

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY

Carlsted

NEW MEXICO

*See Instructions on Reverse Side